



- GENERAL NOTES
- 1 TREATED FINISHED LUMBER ON TRUSSES FOR EXPOSED RAFTER TAILS, PRIMED AND PAINTED PRIOR TO ROOF INSTALLATION.
 - 2 TRUSS MANUFACTURER TO PROVIDE SPECIFIC TRUSS LAYOUT (OWNER TO VERIFY INTEGRITY DESIGN TRUSS PLAN FOR REFERENCE ONLY)
- REFERENCE NOTES
- ROOF NOTES
- SIMPSON H 10 A HURRICANE TIES AT ALL BEARING JOINTS INSTALL TO MANF SPECS
 - ROOF TRUSSES DESIGNED AND ENGINEERED BY MANF TO 140 M.P.H. WIND LOAD
 - INSTALL TRUSSES TO ALL MANF SPECS WALL BRACES, HANGERS, BLOCKS AND TIES SOLID BLOCK ALL BEARING JOINTS.
 - TRUSS SPACING SHALL BE 24" O.C. UNLESS NOTED

1 ROOF FRAMING PLAN (TYPICAL)
SCALE: N.T.S.

P R E L I M I N A R Y
NOT FOR CONSTRUCTION

LAKESHORE BAPTIST CHURCH
FELLOWSHIP HALL AND
CLASSROOMS

PROPOSED ROOF
FRAMING PLAN

I N T E G R I T Y
designs

DATE: 07/28/11
SCALE: 3/16"=1'-0"
DRAWN BY: M. MADISON
JOB: 2011-01

SHEET
A1.5